












Dimensions (mm): 460w x 415d x 800h Weight (kg.): 36

-  Strong 1.5mm mild steel construction
-  Fully powder coated RAL 5010 and RAL 7016
-  Can be either floor standing or wall hung
-  Digital LED Display
-  Single pump
-  Low water cut out to prevent dry running
-  Pump anti-seize pulse
-  Water tank built with type "AA" air gap
-  Fitted with WRAS approved float ball valve (WRAS No. 1011044)

INTRODUCTION

- The EPS is a single pump, single system, electronically controlled pressurisation unit.
- Designed for use on heating or chilled water systems up to and including 2.8 Bar cold fill pressures.
- All mounted in a fully enclosed, mild steel powder coated cabinet.
- The unit is designed for ease of installation with all mechanical connections being terminated outside the main shell.

SYSTEM CONNECTIONS

- 1/2" BSPM connection to float valve
- 1/2" BSPF connection to system
- 22mm compression overflow connection

ELECTRICAL

- Motor: Totally enclosed fan cooled
- Electrical supply: 240 a.c. single phase
- F.L.C.: 2.5 amps / 370w continuously rated
- Motor insulation: IP44 Class F

PIPEWORK

Suction & discharge internal pipework in copper/ plastic capillary tubing, complete with system termination in a 1/2" BSPF.

BREAK TANK

1 No. 4 Gallon polypropylene tank with 1/2" HP float valve and a 22mm compression overflow connection. Type AA air gap and WRAS approved float ball valve.

PUMP

Constructed of a cast iron body with stainless trim, stainless steel shaft with a brass impellor. The pump incorporates a self-adjusting mechanical seal.

VESSELS

A Full range of replaceable bag/diaphragm expansion vessels is available to suit all systems. Range: from 3 to 1000 ltr. (rated at 99°C & 10bar).











CONTROLS

All within the integral enclosure, the controls feature :-

- | | | |
|---|---|---|
| <p>LED Indication for:</p> <ul style="list-style-type: none"> • System Pressure indication • HP — high pressure • LP — low pressure • Transducer fail • Service notification • Fuse/pump fail • Low water | <p>Wiring Terminals for:</p> <ul style="list-style-type: none"> • Boiler/Chiller interlock • Common fault <p>Panel Buttons for:</p> <ul style="list-style-type: none"> • Pump Test • Alarm / Mute | <p>PCB Control for:</p> <ul style="list-style-type: none"> • Anti-seize pulse • Low Water protection • System fill mode |
|---|---|---|

HIGH PRESSURE VERSION AVAILABLE: Model No. EPS-HP
 Suitable for cold fill pressures up to 6.0 Bar / 0.37 kW and 3.41 amps FLC



-  Strong 1.5mm mild steel construction
-  Fully powder coated RAL 5010 and RAL 7016
-  Can be either floor standing or wall hung
-  Digital LED Display
-  Twin pump model
-  Low water cut out to prevent dry running
-  Pump anti-seize pulse
-  Automatic pump rotation
-  Water tank built with type “AA” air gap
-  Fitted with WRAS approved float ball valve (WRAS No. 1011044)

Dimensions (mm): 460w x 415d x 800h Weight (KG): 42

INTRODUCTION

- The EPT is a twin pump, single system, electronically controlled pressurisation unit.
- Designed for use on heating or chilled water systems up to and including 2.8 Bar cold fill pressures.
- All mounted in a fully enclosed, mild steel powder coated cabinet.
- The unit is designed for ease of installation with all mechanical connections being terminated outside the main shell.

SYSTEM CONNECTIONS

- 1/2" BSPM connection to float valve
- 1/2" BSPF connection to system
- 22mm compression overflow connection

ELECTRICAL

- Motor: Totally enclosed fan cooled
- Electrical supply: 240 a.c. single phase
- F.L.C.: 2.5 amps / 370w continuously rated (each pump)
- Motor insulation: IP44 Class F

PIPEWORK

Suction & discharge internal pipework in copper/plastic capillary tubing, complete with system termination in a 1/2" BSPF.

BREAK TANK

1 No. 4 Gallon polypropylene tank with 1/2" HP float valve and a 22mm compression overflow connection.

PUMP

Constructed of a cast iron body with stainless trim, stainless steel shaft with a brass impellor. The pump incorporates a self-adjusting mechanical seal.

VESSELS

A Full range of replaceable bag/diaphragm expansion vessels is available to suit all systems. Range: from 3 to 1000 ltr. (rated at 99°C & 10bar).

CONTROLS

All within the integral enclosure, the controls feature :-

LED Indication for:

- System Pressure indication
- HP — high pressure
- LP — low pressure
- Transducer fail
- Service notification
- Fuse/pump fail
- Low water

Wiring Terminals for:

- Boiler/Chiller interlock
- Common fault

Panel Buttons for:

- Pump 1 Test
- Pump 2 Test
- Alarm / Mute

PCB Control for:

- Pump rotation
- Anti-seize pulse
- Low Water protection
- System fill mode

HIGH PRESSURE VERSION AVAILABLE: Model No. EPT-HP
 Suitable for cold fill pressures up to 6.0 Bar / 0.37 kW and 3.41 amps FLC

Flow Mech Products Ltd., Abbey House, Charter Street, Leicester LE1 3UD

Tel: 0116 242 5425 Fax: 0116 242 5555

Email: info@flowmech.co.uk www.flowmech.co.uk